

Genset model : **QD327E**

Prime power (kVA) **300**

380-415V,50Hz

Standby power (kVA) **327**



www.qaswaa-albararry.com

Prime power : available at variable load. The permissible average power out put (during 24h period) shall not exceed 70% of the prime power rating.

Standby power : available in the event of a main power network failure. No overload is permitted.

Technical Data

Engine model	P126TI-II- DOOSAN
Alternator model	SK250LL- SINCRO
Engine type	In-line 4 cycle, water cooled Turbo charged & intercooled (air to air)
Cylinder type	Replaceable dry liner
No. of cylinder	6
Displacement	11.051(674.5) lit.(in3)
Bore / Stroke	123(4.84) x 155(6.1) mm(in.)
Compression ratio	17 : 1
Insulation class	H
Excitation system	Brushless
Voltage regulator type	AVR BL 4 - B
Short circuit current	> 300 % In
Total harmonic content	< 2 %
Under speed protection	Standard vers.

ENERGY ON DEMAND

FUEL CONSUMPTION (liter/hr)

25%	50%	75%	100%
16.9	31.3	47	63.1

Zexel in-line "P" type	Injection pump	Zexel in-line "P" type
Electric type	Governor	Electric type
Mechanical type	Feed Pump	Mechanical type

