

QASWAA AL-BARARRY



قصواء البراري

ENERGY ON DEMAND
QBO 200 - 220

GENSET-SPECIFICATIONS

• Model	ENERGY ON DEMAND / QBO 200-220	
• Serial number		
• Prime power (KW)	151.0 KWe	
• Prime Capacity (KVA)	208.0 KVA	
• Load Acceptance	189.0 KVA	
• Frequency	50 Hz.	
• Voltage	24 V.	
• Year of Manufacturing	2010	
• Country of origin	Assemble in BAGHDAD	
• Inlet air temperature (c°)	55 c°	
• Relative Humidity	93 % RH @ 40c°	
• Altitude above sea level	1000 Meters	

ENGINE- SPECIFICATIONS

• Engine type (Manufacturer)	Diesel engine	
• Engine model	Perkins 1006C-E87TAG3	
• Serial number		
• Cylinders (No. , Arrangement)	6: Vertical in-line	
• Cycle	4 stroke	
• Compression ratio	16.9:1	
• Torque	N/A	
• Bore and Stroke (mm)	116.6 x 135.9	
• Direction of rotation	Anti-clockwise viewed on flywheel	
• Combustion type	Direct injection	
• Displacement	8.7 liters	
• Engine power (KW)	Gross: 169 KWm	Net: 164 KWm
• Inlet air temperature (c°)	55 c°	
• Relative Humidity	93 % RH @ 40c°	
• Altitude above sea level	1000 Meters	
• Year of Manufacturing	2010	
• Country of origin	United Kingdom. (U.K.)	
• Cooling type	Water cooled	
• Total coolant capacity	37.2 liters	

• Aspiration type	Turbocharged air to air charge cooled		
• Air cooling type	Mounted air filter and turbocharger		
• Water separator	Available		
• Air filter type	Dry		
• Type of fuel governing system	Rotary type pump		
• Speed	1500		
• Type of injection	Fuel injection		
• Silencer type	External		
• Fuel consumption (Full load)	45.2 Liters/hr.		
• Oil consumption	0.1 of fuel consumption		
• Lube oil capacity	26.4 Liters		
• Fuel tank capacity	455 Liters		
• Radiator cooling air flow	375 m ³ /min.		
• Max exhaust gas flow	36.5 m ³ /min.		
• Diesel fuel specification	Diesel fuel according to BS2869 Class or equivalent		
• Lubrication oil specification	Lubricating oil is according to API CH4 (15W/40)		
• Dimensions (mm)	Length: 1822	Width: 875	Height: 1369
• Total weight (Dry)	895.0 kg.		

ALTERNATOR- SPECIFICATIONS

• Type (Manufacturing)	Leroy Somer		
• Country of origin	ALL FACTORIES OF LEROY SOMER IN THE WORLD		
• Model	LSA 46.2 M5		
• Serial number			
• Ratings (KW,KVA – Continues)	175.0 kw	219.0 KVA	
• Voltage line to line	Y 380v.	Δ 230v.	
• Frequency	50 Hz.		
• Number of phases	3 Ph. (Y)		
• Number of poles	4 Poles.		
• Insulation class/ T° rise	H		
• Wires	12		
• Drip proof	IP 23		
• Number of bearings	Single bearing		
• Ambient Temperature (c°)	N/A		
• Relative humidity	92 %		
• Altitude above sea level	1000 Meters		
• Over speed	2250 min ⁻¹		
• Air flow	0.43 m ³ /s.		
• Excitation system	Shunt	Arep or PMG	
• A.V.R. model	R 230	R438	
• Voltage regulation (Steady state)	± 0.5 %		
• Sustained short - Circuit current	300% (3 IN) : 10s		
• Total harmonic (*) TGH/THC	at no load < 2.5 % - on load < 2.5 %		
• Power factor	0.8		

• Efficiency (%) Class (H) at P.F.=0.8	N/A			
• No load Excitation current (A) (SHUNT/AREP)	1			
• Full load Excitation current (A) (SHUNT/AREP)	3.7			
• Full load Excitation voltage (V) (SHUNT/AREP)	32			
• Delivering current to start motor for ten sec.(A)	N/A			
• No load losses (W)	3040			
• Heat rejection (W)	13180			
• Dimensions	L/973	LB/920	XG/470	C/429
• Total weight	625 Kg.			

CONTROL PANEL- SPECIFICATIONS

• Type (Manufacturer)	DEEP SEA ELECTRONIC			
• Model	DSE6110			
• Country of origin	United Kingdom (U.K.)			
• Protections	Available all Options			
• Monitoring	Available			
• Ability of auto starting	Available			
• Programming I/Ps & O/Ps	N/A			
• DC supply range	8v. to 35v. Continuous.			
• Standby current	88mA at 12v.	50mA at 24v.		
• Max. Operation temperature (c°)	+70 c° - Hot	-30 c° - Cold		
• Maximum humidity	93 % RH @ 40c°			
• No. of errors log	More than 20			
• Analogue input range	15v. to 333v.AC(L-N) absolute maximum 50Hz-60Hz (min 15 v. AC)			
• Three Phase current control range (CT input)	Available			
• Generator voltage control range	0.5v. RMS minimum			
• Documentation for the installation and setup	Documented with files			

ATS OR MTS- SPECIFICATIONS

• Type of operation	Auto. & Manual.
• Capacity	9 KVA to 2500 KVA
• Components	Relays, Contactors, Auxiliaries, Timers, Reader, Phase filler, Lamps, Selectors, Emergency stop & Looms.
• Country of origin	Europe.