

QASWAA AL-BARARRY



قصواء البراري

ENERGY ON DEMAND
QBO 250 - 275

GENSET-SPECIFICATIONS

• Model	ENERGY ON DEMAND / QBO 250-275
• Serial number	
• Prime power (KW)	200.0 KWe
• Prime Capacity (KVA)	250.0 KVA
• Load Acceptance	228.0 KVA
• Frequency	50 Hz.
• Voltage	24 V.
• Year of Manufacturing	2010
• Country of origin	Assemble in BAGHDAD
• Inlet air temperature (c°)	55 c°
• Relative Humidity	93 % RH @ 40c°
• Altitude above sea level	1000 Meters

ENGINE- SPECIFICATIONS

• Engine type (Manufacturer)	Diesel engine
• Engine model	Perkins 1006C-E87TAG6
• Serial number	
• Cylinders (No. , Arrangement)	6: Vertical in-line
• Cycle	4 stroke
• Compression ratio	16.9:1
• Torque	N/A
• Bore and Stroke (mm)	116.6 x 135.9
• Direction of rotation	Anti-clockwise viewed on flywheel
• Combustion type	Direct injection
• Displacement	8.7 liters
• Engine power (KW)	Gross: 204 KWm Net: 198 KWm
• Inlet air temperature (c°)	55 c°
• Relative Humidity	93 % RH @ 40c°
• Altitude above sea level	1000 Meters
• Year of Manufacturing	2010
• Country of origin	United Kingdom. (U.K.)
• Cooling type	Water cooled
• Total coolant capacity	37.2 liters

• Aspiration type	Turbocharged air to air charge cooled	
• Air cooling type	Mounted air filter and turbocharger	
• Water separator	Available	
• Air filter type	Dry	
• Type of fuel governing system	Rotary type pump	
• Speed	1500	
• Type of injection	Fuel injection	
• Silencer type	External	
• Fuel consumption (Full load)	45.0 Liters/hr.	
• Oil consumption	0.1 of fuel consumption	
• Lube oil capacity	26.4 Liters	
• Fuel tank capacity	455 Liters	
• Radiator cooling air flow	375 m ³ /min.	
• Max exhaust gas flow	44.5 m ³ /min.	
• Diesel fuel specification	Diesel fuel according to BS2869 Class or equivalent	
• Lubrication oil specification	Lubricating oil is according to API CH4 (15W/40)	
• Dimensions (mm)	Length: 1822	Width: 875 Height: 1369
• Total weight (Dry)	895.0 kg.	

ALTERNATOR- SPECIFICATIONS

• Type (Manufacturing)	Leroy Somer	
• Country of origin	ALL FACTORIES OF LEROY SOMER IN THE WORLD	
• Model	LSA 46.2 L9	
• Serial number		
• Ratings (KW,KVA – Continues)	224.0 kw	280.0 KVA
• Voltage line to line	Y 380v.	Δ 230v.
• Frequency	50 Hz.	
• Number of phases	3 Ph. (Y)	
• Number of poles	4 Poles.	
• Insulation class/ T° rise	H	
• Wires	12	
• Drip proof	IP 23	
• Number of bearings	Single bearing	
• Ambient Temperature (c°)	N/A	
• Relative humidity	92 %	
• Altitude above sea level	1000 Meters	
• Over speed	2250 min ⁻¹	
• Air flow	0.43 m ³ /s.	
• Excitation system	Shunt	Arep or PMG
• A.V.R. model	R 230	R438
• Voltage regulation (Steady state)	± 0.5 %	
• Sustained short - Circuit current	300% (3 IN) : 10s	
• Total harmonic (*) TGH/THC	at no load < 2.5 % - on load < 2.5 %	
• Power factor	0.8	

• Efficiency (%) Class (H) at P.F.=0.8	N/A		
• No load Excitation current (A) (SHUNT/AREP)	1.1		
• Full load Excitation current (A) (SHUNT/AREP)	3.9		
• Full load Excitation voltage (V) (SHUNT/AREP)	33		
• Delivering current to start motor for ten sec.(A)	N/A		
• No load losses (W)	4340		
• Heat rejection (W)	16810		
• Dimensions	L/973	LB/920	XG/485 C/429
• Total weight	775Kg.		

CONTROL PANEL- SPECIFICATIONS

• Type (Manufacturer)	DEEP SEA ELECTRONIC		
• Model	DSE6110		
• Country of origin	United Kingdom (U.K.)		
• Protections	Available all Options		
• Monitoring	Available		
• Ability of auto starting	Available		
• Programming I/Ps & O/Ps	N/A		
• DC supply range	8v. to 35v. Continuous.		
• Standby current	88mA at 12v.	50mA at 24v.	
• Max. Operation temperature (c°)	+70 c° - Hot	-30 c° - Cold	
• Maximum humidity	93 % RH @ 40c°		
• No. of errors log	More than 20		
• Analogue input range	15v. to 333v.AC(L-N) absolute maximum 50Hz-60Hz (min 15 v. AC)		
• Three Phase current control range (CT input)	Available		
• Generator voltage control range	0.5v. RMS minimum		
• Documentation for the installation and setup	Documented with files		

ATS OR MTS- SPECIFICATIONS

• Type of operation	Auto. & Manual.
• Capacity	9 KVA to 2500 KVA
• Components	Relays, Contactors, Auxilarries, Timers, Reader, Phase filler, Lamps, Selectors, Emergency stop & Looms.
• Country of origin	Europe.