

QASWAA AL-
BARARRY



قصواء البراري

ENERGY ON DEMAND
QBO 1250 - 1375

GENSET-SPECIFICATIONS

• Model	ENERGY ON DEMAND / QBO 1250-1375
• Serial number	
• Prime power (KW)	1002.0 KWe
• Prime Capacity (KVA)	1258 KVA
• Load Acceptance	989.0 KVA
• Frequency	50 Hz.
• Voltage	24 V.
• Year of Manufacturing	2010
• Country of origin	Assemble in BAGHDAD
• Inlet air temperature (c°)	
• Relative Humidity	93 % RH @ 40c°
• Altitude above sea level	≤1000 m

ENGINE- SPECIFICATIONS

• Engine type (Manufacturer)	Diesel engine
• Engine model	Perkins 4012TWG2
• Serial number	
• Cylinders (No. , Arrangement)	12: 60° Vee form
• Cycle	4 stroke
• Compression ratio	13.6:1
• Torque	N/A
• Bore and Stroke (mm)	160 x 190
• Direction of rotation	Anti-clockwise viewed on flywheel end
• Combustion type	Direct injection
• Displacement	45.82 liters
• Engine power (KW)	Gross: 1079 KWm Net: 1044 KWm
• Inlet air temperature (c°)	55 c°
• Relative Humidity	93 % RH @ 40c°
• Altitude above sea level	≤1000 m
• Year of Manufacturing	2010
• Country of origin	United Kingdom. (U.K.)
• Cooling type	Water cooled
• Total coolant capacity	185 liters

• Aspiration type	Turbocharged air to water charge cooled		
• Air cooling type	Mounted air filter and turbocharger –Integral charge cooler		
• Water separator	Available		
• Air filter type	Dry		
• Type of fuel governing system	<ul style="list-style-type: none"> ▪ Unit fuel injectors with lift pump and hand stop control ▪ Electronic governor to ISO 3046 Part 4 class A1 ▪ Full-flow spin-on fuel oil filters 		
• Speed	1500		
• Type of injection	Fuel injection		
• Silencer type	External		
• Fuel consumption (Full load)	204 Liters/hr.		
• Oil consumption	0.51 % of fuel consumption		
• Lube oil capacity	177 Liters		
• Radiator cooling air flow	1146 m ³ /min.		
• Max exhaust gas flow	245.0 m ³ /min.		
• Diesel fuel specification	Diesel fuel according to BS2869 Class or equivalent		
• Lubrication oil specification	Lubricating oil is according to API CH4 (15W/40)		
• Dimensions (mm)	Length: 2731	Width: 1541	Height: 2118
• Total weight (Dry)	4400.0 kg.		

ALTERNATOR- SPECIFICATIONS

• Type (Manufacturing)	Leroy Somer	
• Country of origin	ALL FACTORIES OF LEROY SOMER IN THE WORLD	
• Model	LSA 50.1 M6	
• Serial number		
• Ratings (KW,KVA – Continues)	980.0 kw	1225.0 KVA
• Voltage line to line	Y 380v.	Δ 230v.
• Frequency	50 Hz.	
• Number of phases	3 Ph. (Y)	
• Number of poles	4 Poles.	
• Insulation class/ T° rise	H	
• Wires	12	
• Drip proof	IP 23	
• Number of bearings	Single bearing	
• Ambient Temperature (c°)	55 c°	
• Relative humidity	92 %	
• Altitude above sea level	1000 Meters	
• Over speed	2250 min ⁻¹	
• Air flow	1.6 m ³ /s.	
• Excitation system	Shunt	Arep or PMI
• A.V.R. model	---	R449
• Voltage regulation (Steady state)	± 0.5 %	
• Sustained short - Circuit current	300% (3 IN) : 10s	
• Total harmonic (*) TGH/THC	< 4 %	
• Power factor	0.8	

Efficiency (%) Class (H) at P.F.=0.8	75%= 95.4	100%= 94.7				
• No load Excitation current (A) (SHUNT/AREP)	1.1					
• Full load Excitation current (A) (SHUNT/AREP)	4.9					
• Full load Excitation voltage (V) (SHUNT/AREP)	62					
• Delivering current to start motor for ten sec.(A)	N/A					
• No load losses (W)	13705					
• Heat rejection (W)	52665					
• Dimensions	L- 1641	LB- SAE00 1575	LB- SAE0 1600	C- SAE00 800	C- SAE0 825	XG- 686
• Total weight	2420 Kg.					

CONTROL PANEL- SPECIFICATIONS

• Type (Manufacturer)	DEEP SEA ELECTRONIC	
• Model	DSE6110	
• Country of origin	United Kingdom (U.K.)	
• Protections	Available all Options	
• Monitoring	Available	
• Ability of auto starting	Available	
• Programming I/Ps & O/Ps	N/A	
• DC supply range	8v. to 35v. Continuous.	
• Standby current	88mA at 12v.	50mA at 24v.
• Max. Operation temperature (c°)	+70 c° - Hot	-30 c° - Cold
• Maximum humidity	93 % RH @ 40c°	
• No. of errors log	More than 20	
• Analogue input range	15v. to 333v.AC(L-N) absolute maximum 50Hz-60Hz (min 15 v. AC)	
• Three Phase current control range (CT input)	Available	
• Generator voltage control range	0.5v. RMS minimum	
• Documentation for the installation and setup	Documented with files	

ATS OR MTS- SPECIFICATIONS

• Type of operation	Auto. & Manual.
• Capacity	9 KVA to 2500 KVA
• Components	Relays, Contactors, Auxilarries, Timers, Reader, Phase filler, Lamps, Selectors, Emergency stop & Looms.
• Country of origin	Europe.