



MOTOR VX 20W50

20W50 MOTOR OIL FOR DIESEL AND GASOLINE ENGINES

APPLICATIONS

MOTOR VX 20W50 has been formulated to lubricate a large range of engines, **turbo charged or not**, running any time of the year. It ensures a good cold start. This oil meets with the requirements of engines operating under normal conditions of use, and in particular at high temperatures.

MOTOR VX 20W50 guarantees the oil pressure maintenance and ensures the motor long life.

ADVANTAGES

MOTOR VX 20W50 has been prepared from carefully selected base oils and additives in order to comply with its expected conditions of use.

PERFORMANCE DETAILS

MOTOR VX 20W50 meets with the following international standards:

ACEA A2/E2/B2

API CF/CF4/SJ

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	20W50
Specific gravity at 15°C	kg/m ³	NF T 60101	890
Kinematic viscosity at 40°C	mm ² /s	NF T 60100	169.3
Kinematic viscosity at 100°C	mm ² /s	NF T 60100	18.6
Viscosity index	-	NF T 60136	124
Dynamic viscosity at -10°C	mPa.s	ASTM D 2602	3.900
Pour point	°C	NF T 60105	-27
Flash point VO	°C	NF T 60118	234
TBN	mgKOH/g	ASTM D 2896	11.1

This typical data is given for information only.

GBVX2050-A1-07/2007

1/2

UNIL OPAL

Z.I. Clos Bonnet / Boulevard Jean Moulin - B.P. 88 - 49403 SAUMUR cedex - FRANCE - Téléphone : 02.41.40.18.40 - Fax : 02.41.50.52.43
Beauvais (60) - La Chapelle (59) - Lamanon (13) - Poitiers (86) - Puisieux (45) - E-mail : info@unil-opal.fr

► N° Indigo 0 825 825 925
0,150 € TTC / MN





FICHE TECHNIQUE

MOTOR VX 20W50

HEALTH, SAFETY AND ENVIRONMENT

Elimination must be carried out to conform to the rules set for the disposal of used mineral oils.

Must be stored away from bad weather.

Should you need further details, our Technical Department remains at your disposal.

GBVX2050-A1-07/2007

2/2

UNIL OPAL

Z.I. Clos Bonnet / Boulevard Jean Moulin - B.P. 88 - 49403 SAUMUR cedex - FRANCE - Téléphone : 02.41.40.18.40 - Fax : 02.41.50.52.43
Beauvais (60) - La Chapelle (59) - Lamanon (13) - Poitiers (86) - Puiseaux (45) - E-mail : info@unil-opal.fr

► N° Indigo 0 825 825 925
0,150 € TTC / MN

