



OPALJET LONGLIFE 3

100 % SYNTHETIC OIL
FOR LONGER DRAIN PERIODS FOR BMW AND OPEL

APPLICATIONS

OPALJET LONGLIFE 3 is a multigrade high performance, oil specially formulated to lubricate the new generation of Turbo Diesel engines equipped with pump injector and to extend the life duration of after-treatment (especially particles filters).

ADVANTAGES

5W30 : This grade protect your engine when starting from the extreme cold (-30°) and allows a significant fuel economy compared to the use of 15W40.

OPALJET LONGLIFE 3 meets the classifications API SM/CF and ACEA C3/A3/B4. It offers the most reliable guarantee of highest quality and special formulation.

Its good thermal stability and its high performant specific additives make **OPALJET LONGLIFE 3** the **ideal lubricant for the most sophisticated engines** :

- VW engines
- BMW engines with longer drain periods
- GM (OPEL) engines with longer drain periods

OPALJET LONGLIFE 3 insures **particles filters protection** and 3 way catalysts against gumming-up.

PERFORMANCE DETAILS

OPALJET LONGLIFE 3 is approved (1):

VW 505.01* BMW LONGLIFE-04* MB 229.51 OPEL 2010*

OPALJET FUTURA meets the following international classifications and specifications:

ACEA C3-08 ACEA A3/B4-08 API SM/CF VW 502.00 / 505.00

In-use experience of OPALJET LONGLIFE 3 allows to recommend it when the following performance level is required : ACEA C2-08

(1) Approval certificates available on request.
* in progress

GBLONGLIFE3-A1-05/2010

1/2



FICHE TECHNIQUE

OPALJET LONGLIFE 3

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	5W30
Specific gravity at 15°C	kg/m ³	NF T 60-101	852
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	70.8
Kinematic viscosity at 100°C	mm ² /s	NF T 60-100	12.2
Viscosity index	-	NF T 60-136	171
CCS viscosity at -30°C	mPa.s	ASTM D 5293	6280
Flash point	°C	NF T 60-118	234
Pour point	°C	NF T 60-105	- 33
TBN	mg KOH/g	ASTM D 2896	7.2

This typical data is given for information only

HEALTH, SAFETY AND ENVIRONMENT

Elimination must be carried out to conform to the rules set for the disposal of used lubricants.

Must be stored away from bad weather.

Should you need further details, our Technical Department remains at your entire disposal.

GBLONGLIFE3-A1 -05/2010

2/2

UNIL OPAL

Z.I. Clos Bonnet / Boulevard Jean Moulin - B.P. 88 - 49403 SAUMUR cedex - FRANCE - Téléphone : 02.41.40.18.40 - Fax : 02.41.50.52.43
Beauvais (60) - La Chapelle (59) - Lamanon (13) - Poitiers (86) - E-mail : info@unil-opal.fr

N° Indigo 0 825 825 925
0,180 € TTC / MN

